

60 Degree Gloss Meter MG6-F1



Technical Specifications:

Technical Specification	Units	Specification
Reading Range	GU	0.0~ 200
Indication Error	GU	±1.2
Measuring Area	mm ²	20mm×10mm
Incidence Angle	Deg.	60
Volume (L×W×H)	mm ³	123×38×65
Main Weight	g	300
Power Supply	V	One AA-size battery

It is designed and manufactured according to ISO2813 is compatible with the standards of ASTM D2457 and ASTM D523.

Applications:

- Most common surfaces such as paints, varnishes, ink, plastics, etc.
- Decorative materials, such as marble, granite, and ceramic tile.

Features:

- Simple to Use, Small, Smart, and Stable.
- A single AA size battery (Rechargeable or alkaline).

Guarantee:

- One Year

Terms and Conditions:

Purchase orders are subject to Janda Corporation credit department approval. Freight is prepaid and added. Title to merchandise transfers to purchaser upon delivery to the carrier. Responsibility for loss or damage in transit is with purchaser. Software licensed to original purchaser. A one-year warranty applies to all new equipment. Applicable sales tax to apply. FOB Annapolis, MD 21403 USA. Payment Terms Net 30 Days.

SEND PURCHASE ORDER TO: JANDA CORPORATION, 301 Burnside Street Suite C-101, ANNAPOLIS, MD 21403-6314 USA

TELEPHONE: 410-263-2223 FAX 410-975-4636 Email Contact: BobJanda@JandaCorp.net